



NOTES:


- 1. WHEN DIRECTED BY LBWD AND PRIOR TO FINAL PAVING, REMOVE GATE BOX AND PLACE GATE BOX LID ON POLYVINYL CHLORIDE PIPE RISER.
- 2. REFER TO SPECIFICATION SECTION 09 90 00 FOR COATING OF STEEL PIPE.






NOTE:

BRASS CAP SHALL BE IN PLACE AT ALL TIMES.







2" AIR RELIEF AND VACUUM VALVE ASSEMBLY

THIS DETAIL FOR BACK OF CURB LINE APPLIES IF PLANS INDICATE IT TO BE A 2" AUTOMATIC AIR RELIEF AND VACUUM VALVE ASSEMBLY

NOTES:

- 1. ALL PIPING TO BE COPPER PIPE.
- COAT ALL FITTINGS, VALVES, AND BOLTED COUPLINGS WITH NO-OX-ID A SPECIAL COMPOUND AND WRAP WITH NO-OX-ID TAPE.
- 3. REFER TO SPECIFICATION SECTION 09 90 00 FOR COATING OF VALVE HOUSING.
- 4. VALVE HOUSING SHALL BE SAND BLASTED INSIDE AND OUTSIDE BEFORE PAINTING OUTSIDE PER SPECIFICATION SECTION 09 90 00.





2" AIR RELIEF ASSEMBLY



Exceptional Water • Exceptional Service

DIRECTOR OF ENGINEERING


DEPUTY GENERAL MANAGER / CHIÉF ENGINEER

WDS - 212


APPROVED


DATE: 02-2020 SCALE: N.T.S.

SHEET 4 OF 5



VALVE HOUSING





BRACKET DETAIL FOUR (4) REQUIRED

